

VP-1100 2nd Monitor



VP-1100-2ND-10.1

FEATURES

- VGA Interface Available
- Outstanding Brightness reaches 400 Nits.
- Chassis Color for optional

SPECIFICATIONS



DISPLAY

Display Area
Resolution
Brightness/Backlight Type
Contrast Ratio
Response Time
Viewing Angle
I/O Connection

10.1 Inch
1280 x 800
400cd m2 (LED)
600 : 1
25 ms
80° /80° /80° /80°
1 x VGA / 1 x 12V DC Input

PHYSICAL

Housing Material
Tilt Angle
VESA Mounting
Dimensions (W x D x H)
Packing Dimension
Net Weight
Gross weight

Plastic
0 - 270°
75mm x 75mm
263 (W) x 22 (D) x 178 (H) mm
320 (W) x 65 (D) x 222 (H) mm
N.W. 0.82 Kg
G.W. 1.00 Kg

ENVIRONMENTAL

Consumption
Operating Temperature
Storage Temperature
Humidity
Shock / Drop

25 MAX
0°C ~ 50°C
0°C - 60°C
10% - 85%
Prohibited

POWER

Power Input

12V - 2A

*All rights reserved. All specifications are subject to change without notice. 保留隨時更改本文中產品相關描述之權利，若有更改恕不另行通知。

Asia, Pacific & Europe: Unit A, 2/F., Mai Tak Industrial Building #221 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong

Tel: (852) 3590 6397 | Fax: (852) 3590 6497 | www.eclinepos.com | sales@ecline.com.hk