

2D Image Scanner



EC-2D-8300

Features

- Support 1D and 2D Barcode
- Automatic Detect Reading Mode
- 3 in 1 combo Interface - change interface by replacing cable
- Colored Aiming Blue Light



Specifications

Scan Type	2D Image
CMOS	640 X 480
Motion Tolerance	Up to 450 cm/s for 13 mil UPC at optimal focus
Scan Angle	Horizontal 45°; Vertical: 45°
Print Contrast	20% Minimum Reflectance Difference
Pitch, Skew	45°, 65°
Decode	ALL 1D, PDF, ALL 2D
Operating Temperature	0°C to 50°C (32°F to 122°F)
Storage Temperature	-40°C to 70°C (-40°F to 158°F)
Humidity	0% to 95% relative humidity, non-condensing
Drop	50 2m drops to concrete
Environmental Sealing	IP54
Light Levels	100,000 Lux
Input Voltage	5 VDC to 5.5 VDC
Operating Power	2. W (420mA @ 5 VDC)
Standby Power	0.45 W (80mA @ 5 VDC)
Dimensions (L x W x H)	180×70×80 mm
Weight	Scanner : 150g

Asia, Pacific & Europe: Unit A, 2/F., Mai Tak Industrial Building #221 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong
Tel: (852) 3590 6397 | Fax: (852) 3590 6497 | www.eclinepos.com | sales@ecline.com.hk

México, E.U.A, Latinoamérica: Nueva Irlanda #4057, Fracc. Industrial Lincoln, C.P. 64310, Monterrey, N.L. México.
+52 (81) 8370-5096 | 01 800 509-1818 | www.eclinepos.com | ventas@ecline.com.mx