

Label Pinter



EC-3150D-USB

Features

- 3inch print width
- 6inch / sec ultra high print speed
- Support 2D barcode printing
- Label paper auto positioned
- Compatible with various label software
- BMP, PCX, BAS files download and storage supported
- Suport print media en 16mm to 82mm range, easy operation design
- Paper auto checkout and temperature auto controlled function
- Compatible with variuos label software



Specifications

Print method
Print width
Resolution
Print speed
Interface
Media
Print head
Paper presence
Enlargement
Barcode type

Character size
Fonts
Data
NV Flash
Cashdrawer out
Power supply
Power adaptador
Weight
Dimension
Work enviroment
Storage enviroment
Mechanism

Direct thermal line
3inch
203dpi
3~6inch/s
Serial+USB+Ethernet / Parallel+USB
Diameter: 25~85mm; Width: 16~82mm
Temperature sensor: thermal sensitive resistance; Pision sensor: microswitch
Photoelectricity sensor
1to 10 times enlargement in both directions. 0°, 90°, 270°, 360° rotation
CODE128/EAN128/ITF/CODE39/CODE93/EAN13/EAN13+2/EAN13+5/EAN8/EAN8+2
EAN8+5/CODABAR/POSTNET/UPC-A/UPC+2/UPC+5/UPC-E/UPCE+2/UPC-E+5
CPOST/MSI/MSIC/PLESSEY/ITF14/EAN14/QRCODE(GP-3150TI)
FONT 0 to FONT 8 Simplified/Traditional Chinese/ Korean
GB2312
2M bytes
2M bytes
DC 24V/1A
DC 24V/2A
Input: AC 110V/220V, 50~60Hz Output:DC 24V/2A
1.65KG
230 x 156 x 147mm (L x W x H)
Temperature: 0~45°C, Humidity: 10~80%
Temperature: -10~60°C, Humidity: 10~90%
150 Km

Asia, Pacific & Europe: Unit A, 2/F., Mai Tak Industrial Building #221 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong
Tel: (852) 3590 6397 | Fax: (852) 3590 6497 | www.eclinepos.com | sales@ecline.com.hk

México, E.U.A, Latinoamérica: Nueva Irlanda #4057, Fracc. Industrial Lincoln, C.P. 64310, Monterrey, N.L. México.
+52 (81) 8370-5096 | 01 800 509-1818 | www.eclinepos.com | ventas@ecline.com.mx