


APEXA® TL-1500

Tiger Lake Compact POS

APEXA® TL-1500 is a premium all-in-one POS terminal powered by Intel's 11th Gen. Tiger Lake.

The compact monitor screen allows users to make practical use of limited space.

It can create a sophisticated interior design in a modern and contemporary style, and is optimized for large-scale distribution, dining, specialty stores, and franchise industries.



APEXA® TL-1500 Features & Benefits



The latest Intel 11th Gen. Tiger lake

- Higher-performance computing and graphics
- POS systems for retail and QSR

Fast installation and maintenance

- Spacious I/O ports placed on top for easy access
- Reduced maintenance costs

Liquid ingress protection design

- Prevents the ingress of various liquids and protection design foreign substances
- More suitable for food and beverage service environments

APEXA® TL-1500 Specifications

System	Processors	Intel® Core™ i3-1115G4 Processor 6M Cache, up to 4.10 GHz	
	Chipset	Intel® Tiger Lake	
	Memory	4GB Standard, DDR4 3200 MT/s, Socket 1 x SODIMM (Max. 32GB)	
	Storage	SATA 3 (6Gb/s) 2.5 inch SSD 64GB, Support AHCI	
	RAID	RAID 0,1	
	Operating Systems	Windows 10 IoT Enterprise	
	Audio	HD Audio Codec	
Display	Type	15" TFT LCD, LED Backlight	
	Resolution	1024 x 768	
	Brightness	300 cd/m ² (typ.)	
	Touchscreen	Projected Capacitive Touch	
Interface	Display	VGA x 1 (With Power Output)	
	USB	6 (Rear 2, Back 4, USB 3.0 x 2, USB 2.0 x 2) 3 (Reserved for MSR, SCR, i-Button/Touch Controller/Camera), RJ-45	
	Serial	6 (COM1 with 5V/12V Power Output on 9 Pins, BIOS) (COM2~3 RJ-45, Full Signal) (COM4 RJ-11, Only TX/RX, 12V Power Output, Reserved for CDP) (COM5, Full Signal) (COM6 RJ-45, Only TX/RX, 5V Power Output, Reserved for MSR)	
	Back I/O	Cash Drawer Port(GPIO Communication) (RJ-11 6 Pins) x 1 + USB 2.0 x 2 (Default)	
	Optimal I/O	Gigabit Ethernet x 1 (RJ-45) + USB 2.0 x 2 (Factory option) 12V Powered USB 2.0 x 1 + 24V Powered USB 2.0 x 1 (Factory option) 12V Powered USB 2.0 x 1 + 12V Powered USB 2.0 x 1 (Factory option) 24V Powered USB 2.0 x 1 + 24V Powered USB 2.0 x 1 (Factory option) 12V Powered USB 2.0 x 1 + USB 2.0 x 1 (Factory option) 24V Powered USB 2.0 x 1 + USB 2.0 x 1 (Factory option) COM5 x 1 (RJ-45, Full signal) + USB 2.0 x 2 (Factory option) USB A 2.0 x 4 (Factory option) One option attachable at a time	
	LAN	Gigabit Ethernet x 1 (RJ-45)	
	Audio	Line-out x 1	
	Power DC-IN	3 Pin DIN Jack	
	Extension Slot	M.2 for WiFi/BT, SSD	
	Power	Power Supply	Adapter 24V, 2.5A (Nomarl) / 24V, 6.35A(Powered USB Option)
	Physical & Environmental	Operating Temperature	0°C ~ 60°C at 10% to 90% Humidity
Storage Temperature		-20°C ~ 80°C at 10% to 90% Humidity	
Dimensions (W x H x D)		364 x 333 x 210 (mm), 14.3 x 13.1 x 8.2(in)	
Packing Dimensions (W x H x D)		500 x 470 x 300 (mm), 19.6 x 18.5 x 11.8(in)	
Net Weight		5,300g, 11.68 lbs	
Packing Weight		8,000g, 17.63 lbs	
Color		Dark Grey, High Gloss White	
Options & Peripherals	2nd Displays	9.7", 15" LCD Display, 1024 x 768, Optional Touchscreen	
	Customer Display	VFD, 20 Columns x 2 Lines	
	Storage	2.5 inch SSD 128GB, HDD 500GB, 1TB	
	Magnetic Stripe Reader	Comply with ISO 7811, Support 1 & 2 & 3 Track	
	Smart Card Reader	EMV Level 1	
	Dallas	Dallas i-button Reader	
	Fingerprint	Yes	
	Wall Mount Kit	VESA-Compatible, 75 x 75(mm), 100 x 100(mm)	
	Serial Conversion Cable	RJ-45 to D-sub 9	
	Speaker	2 x 1W (Stereo) (Factory Option)	
	WiFi/BT	M.2 for WiFi/BT	
TPM	Support		

EC Electronics, Limited
(852) 3590 6397
(852) 3590 6497

www.ecline.com.hk sales@ecline.com.hk
Unit A, 2/F, Mai Tak Industrial Building,
No. 221 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong

POSBANK®

POSBANK and the POSBANK logo are trademarks of POSBANK in the United States and other countries. All trademarks are the property of their respective owners. Intel, Celeron, Core are registered trademarks of Intel Corporation in the United States and other countries. Microsoft, Windows 7, Windows 8.1, Windows 10 IoT Enterprise and POS Ready 7 are registered trademarks of Microsoft Corporation in the United States and other countries. POSBANK shall not be liable for technical or editorial errors or omission contained herein. The information in this publication is informational purposes only and may be altered or amended by POSBANK. All statements regarding POSBANK's direction and intent are subject to change or withdraw without notice. Specifications may change without prior notice.